


VITI A ESAGONO INTERNO


Tabella N. 7

Diametro viti corrispondente all'inserto esagonale

Misure metriche

 Ø Viti mm	 mm 		
			
	Viti a testa cilindrica	Viti a testa fresata	Viti senza testa ISO 4026
1,6	1,5		0,7
2	1,5		0,9
2,5	2		1,3
3	2,5	2	1,5
4	3	2,5	2
5	4	3	2,5
6	5	4	3
8	6	5	4
10	8	6	5
12	10	8	6
14	12	10	
16	14	10	8
18	14		
20	17	12	10
22	17		
24	19		12
27	19		
30	22		
33	24		
36	27		
42	32		

Misure in pollici


 Ø Viti mm	 " 					
						
	Viti a testa cilindrica		Viti a testa fresata		Viti senza testa ISO 4026	
n° 0	1,52	0,50	1,27	,035	0,89	,028
n° 1	1,85	1/16	1,59	,050	1,27	,035
n° 2	2,18	5/64	1,98	,050	1,27	,035
n° 3	2,51	5/64	1,98	1/16	1,59	,050
n° 4	2,84	3/32	2,38	1/16	1,59	,050
n° 5	3,17	3/32	2,5	5/64	1,98	1/16
n° 6	3,5	7/64	3	5/64	1,98	1/16
n° 7	3,5	1/8	4			
n° 8	4,16	9/64	5	3/32	2,38	5/64
n° 10	4,82	5/32	6	7/64	2,78	3/32
n° 10	4,82		1/8	3,17		
1/4	6,35	3/16	4,75	9/64	3,57	7/64
1/4	6,35	7/32	5,55	5/32	3,97	1/8
5/16	7,94	1/4	6,35	3/16	4,75	9/64
5/16	7,94					5/32
3/8	9,52	5/16	7,94	7/32	5,55	3/16
7/16	11,11	3/8	9,52	1/4	6,35	7/32
1/2	12,7	3/8	9,52	5/16	7,94	1/4
5/8	15,87	1/2	12,7	3/8	9,52	5/16
3/4	19,05	5/8	15,88	1/2	12,7	3/8
7/8	22,2	3/4	19,05	9/16	14,29	1/2
1	25,4	3/4	19,05	5/8	15,88	9/16
1"1/8	28,57	7/8	22,2	3/4	19,05	9/16
1"1/4	31,75	7/8	22,2	7/8	22,2	5/8
1"3/8	34,92	1"	25,4	7/8	22,2	5/8
1"1/2	38,10	1"	25,4	1"	25,4	3/4

VITI CON IMPRONTA TORX

Tabella N. 8

Diametro viti corrispondente all'impronta TORX


Corrispondenza diametro della vite e chiave maschio TORX®

 Ø Viti mm	 Torx 			
				
	Testa cilindrica	Testa bombata	Testa fresata	Senza testa
2		T6	T6	
2,5	T8	T8	T8	
3	T10	T10	T10	T6
3,5		T10	T10	
4	T25	T20	T20	T8
5	T25	T20	T20	T10
6	T30	T30	T30	T20
8	T40	T40	T40	T27
10	T50	T50	T50	T30
12	T55	T55	T55	T45
16	T60	T60	T60	T50

Identificazione dell'impronta maschio

Torx	 mm
T6	1,75
T8	2,39
T10	2,82
T15	3,35
T20	3,94
T25	4,52
T27	5,08
T30	5,61
T40	6,76
T45	7,92
T50	8,94
T55	11,33
T60	13,44

Corrispondenza diametro delle viti e bussole TORX®

 Ø Viti mm		
		
	ISO 4014 ISO 4017	Collarino largo
3	E4	
4	E5	E6
5	E6	E8
6	E8	E10
8	E10	E12
10	E12	E14
12	E14	E18
14	E18	E20
16	E20	