

Misure barrate **ESAURITE**

Tipo per SEMIFINIRE a taglienti elicoidali. Serie corta.
DIN 845 B - UNI 8250 - ISO 1641/2. Attacco Cono Morse e foro filettato.
Tolleranza tagli. J14.

Ø mm 16 a 22 = 4 tagli./Ø mm 24 a 32 = 5 tagli.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 5%.

Ø	mm	16	18	20	22	26	28	30	32
Lungh. totale	mm	117	117	123	140	147	147	147	178
Lungh. tagliente	mm	32	32	38	38	45	45	45	53
Attacco	C.M.	2	2	2	3	3	3	3	4
8763	Cad.	99,20	110,00	120,00	226,00	276,00	303,00	343,00	417,00

Articolo in esaurimento.

SCU

8763



HSS-E-5%

Descrizione di riferimento vedi Art. 8763

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø	mm	16	18	20	22	24	26	28	30	32
Lungh. totale	mm	117	117	123	140	147	147	147	155	178
Lungh. tagliente	mm	32	32	38	38	45	45	45	53	53
Attacco	C.M.	2	2	2	3	3	3	3	3	4
8764	Cad.	138,00	138,00	185,00	199,00	220,00	245,00	262,00	291,00	348,00

SCU

8764



HSS-E-8%

Tipo per SGROSSARE a taglienti elicoidali. Serie corta.

DIN 844 A - UNI 8244 A - ISO 1641/1. Attacco DIN 6535 HB/1835-1B. Tolleranza tagli. J14.

Ø mm 6 = 3 tagli./Ø mm 8 a 22 = 4 tagli./Ø mm 25-30 = 5 tagli.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø	mm	6	8	10	12	14	15	16
Lungh. totale	mm	57	69	72	83	83	83	92
Lungh. tagliente	mm	13	19	22	26	26	26	32
Attacco Ø	mm	6	10	10	12	12	16	16
8766	Cad.	45,40	67,10	67,10	75,30	84,80	104,00	98,60

SCU

8766



HSS-E-8%

Ø	mm	18	20	22	25	30
Lungh. totale	mm	92	104	104	121	121
Lungh. tagliente	mm	32	38	38	45	45
Attacco Ø	mm	16	20	20	25	25
8766	Cad.	105,00	129,00	145,00	209,00	260,00

Tipo per SGROSSARE a taglienti elicoidali. Serie corta.

DIN 844 A - UNI 8244 A - ISO 1641/1. Attacco DIN 6535 HB/1835-1B. Tolleranza tagli. J14.

Ø mm 10 a 20 = 4 tagli./Ø mm 25-30 = 5 tagli.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8% con rivestimento TiAIN.

Ø	mm	10	12	14	16	18	20
Lungh. totale	mm	72	83	83	92	92	104
Lungh. tagliente	mm	22	26	26	32	32	38
Attacco Ø	mm	10	12	12	16	16	20
8766E	Cad.	83,20	94,60	108,00	133,00	141,00	165,00

SCU

8766E



TiAIN

HSS-E-8%

Tipo per SGROSSARE a taglienti elicoidali. Serie lunga.

Attacco DIN 6535 HB/1835-1B. Tolleranza tagli. J14.

Ø mm 10 = 3 tagli./Ø mm 10 a 22 = 4 tagli./Ø mm 25 = 5 tagli.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø	mm	8	10	12	14	15	16	18
Lungh. totale	mm	88	95	110	110	110	123	123
Lungh. tagliente	mm	38	45	53	53	53	63	63
Attacco Ø	mm	10	10	12	12	16	16	16
8768	Cad.	91,10	92,20	111,00	115,00	134,00	134,00	147,00

SCU

8768



HSS-E-8%

Ø	mm	20	22	25
Lungh. totale	mm	141	151	166
Lungh. tagliente	mm	75	75	90
Attacco Ø	mm	20	20	25
8768	Cad.	172,00	214,00	284,00

Tutte le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.

Prezzi in EURO - IVA esclusa