

9212G 
**M****HSS-E**

Orig. Völkel - Art. 384

GAMBO PASSANTE

USO DESTRO

FILETTATURA METRICA ISO-Conforme DIN 13 (DIN 376)-Metrico Grosso M-Tolleranza ISO2/6H.

HSS-E. Imbocco corto. Tipo universale. Fori ciechi e passanti.

Ø.....	mm	3	4	5	6	8	10	12	14	16
Passo.....	mm	0,5	0,7	0,8	1	1,25	1,5	1,75	2	2
Lungh. totale.....	mm	56	63	70	80	90	100	110	110	110
Lungh. filetto.....	mm	11	13	16	19	22	24	29	30	32
Ø gambo.....	mm	2,2	2,8	3,5	4,5	6	7	9	11	12
Quadro gambo.....	mm	-	2,1	2,7	3,4	4,9	5,5	7	9	9

9212G

Cad.

10,40	10,40	11,10	11,10	15,60	19,30	22,10	26,70	30,10
--------------	--------------	--------------	--------------	--------------	--------------	--------------	--------------	--------------

Ø.....	mm	18	20	22	24	27	30	33	36
Passo.....	mm	2,5	2,5	2,5	3	3	3,5	3,5	4
Lungh. totale.....	mm	125	140	140	160	160	180	180	200
Lungh. filetto.....	mm	34	34	34	38	38	45	50	56
Ø gambo.....	mm	14	16	18	18	20	22	25	28
Quadro gambo.....	mm	11	12	14,5	14,5	16	18	20	22

9212G

Cad.

55,20	96,10	117,00	153,00	188,00	235,00	290,00	352,00
--------------	--------------	---------------	---------------	---------------	---------------	---------------	---------------

9213G 
**M****USO SINISTRO****HSS-E**

Orig. Völkel - Art. 344

GAMBO PASSANTE

USO SINISTRO

FILETTATURA METRICA ISO-Conforme DIN 13 (DIN 376)-Metrico Grosso M-Tolleranza ISO2/6H.

HSS-E. Imbocco corto. Tipo universale. Fori ciechi e passanti.

Ø.....	mm	12	14	16	18	20	22	24
Passo.....	mm	1,75	2	2	2,5	2,5	2,5	3
Lungh. totale.....	mm	110	110	110	125	140	140	160
Lungh. filetto.....	mm	29	30	32	34	34	34	38
Ø gambo.....	mm	9	11	12	14	16	18	18
Quadro gambo.....	mm	7	9	9	11	12	14,5	14,5

9213G

Cad.

42,60	55,90	83,20	109,00	147,00	178,00	191,00
--------------	--------------	--------------	---------------	---------------	---------------	---------------

9218G 
**M****HSS-E**

Orig. Völkel - Art. 385

GAMBO PASSANTE

USO DESTRO

FILETTATURA METRICA ISO-Conforme DIN 13 (DIN 376)-Metrico Grosso M-Tolleranza ISO2/6H.

HSS-E. Imbocco corretto. Per metalli fino a R 900 N/mm², acciai legati e non legati. Fori passanti.

Ø.....	mm	3	4	5	6	8	10	12	14	16
Passo.....	mm	0,5	0,7	0,8	1	1,25	1,5	1,75	2	2
Lungh. totale.....	mm	56	63	70	80	90	100	110	110	110
Lungh. filetto.....	mm	11	13	16	19	22	24	29	30	32
Ø gambo.....	mm	2,2	2,8	3,5	4,5	6	7	9	11	12
Quadro gambo.....	mm	-	2,1	2,7	3,4	4,9	5,5	7	9	9

9218G

Cad.

10,80	10,80	11,70	11,90	15,20	20,40	24,50	29,60	33,10
--------------	--------------	--------------	--------------	--------------	--------------	--------------	--------------	--------------

Ø.....	mm	18	20	22	24	27	30	33	36
Passo.....	mm	2,5	2,5	2,5	3	3	3,5	3,5	4
Lungh. totale.....	mm	125	140	140	160	160	180	180	200
Lungh. filetto.....	mm	34	34	34	38	38	45	50	56
Ø gambo.....	mm	14	16	18	18	20	22	25	28
Quadro gambo.....	mm	11	12	14,5	14,5	16	18	20	22

9218G

Cad.

60,70	96,10	117,00	153,00	188,00	235,00	290,00	386,00
--------------	--------------	---------------	---------------	---------------	---------------	---------------	---------------

9220G 
**M****HSS-E**

Orig. Völkel - Art. 389

Descrizione di riferimento vedi Art. 9218G

HSS-E. Imbocco corto. Tipo Allzwek con filetti alternati, per metalli fino a R 900 N/mm², acciai legati e non legati. Fori passanti.

Ø.....	mm	3	4	5	6	8	10	12
Passo.....	mm	0,5	0,7	0,8	1	1,25	1,5	1,75
Lungh. totale.....	mm	56	63	70	80	90	100	110
Lungh. filetto.....	mm	11	13	16	19	22	24	29
Ø gambo.....	mm	2,2	2,8	3,5	4,5	6	7	9
Quadro gambo.....	mm	-	2,1	2,7	3,4	4,9	5,5	7

9220G

Cad.

17,40	17,40	19,70	21,30	26,80	33,90	43,30
--------------	--------------	--------------	--------------	--------------	--------------	--------------

Ø.....	mm	14	16	18	20	22	24
Passo.....	mm	2	2	2,5	2,5	2,5	3
Lungh. totale.....	mm	110	110	125	140	140	160
Lungh. filetto.....	mm	30	32	34	34	34	38
Ø gambo.....	mm	11	12	14	16	18	18
Quadro gambo.....	mm	9	9	11	12	14,5	14,5

9220G

Cad.

56,70	75,60	101,00	133,00	145,00	177,00
--------------	--------------	---------------	---------------	---------------	---------------