

9364G



Orig. Völkel - Art. 234

Descrizione di riferimento vedi Art. 9350G

FILETTATURA AMERICANA UNC conforme ANSI-B1.1

USO DESTRO

In acciaio SUPER-RAPIDO HSS, imbocco normale, per acciai con R fino a 800 N/mm².

Filett. UNC.....		Nr. 1	Nr. 2	Nr. 3	Nr. 4	Nr. 5	Nr. 6	Nr. 8
Filetti per pollice	Nr	64	56	48	40	40	32	32
Dimensioni.....	mm	16x5	16x5	16x5	20x5	20x5	20x7	20x7
9364G	Cad.	20,80	20,80	20,20	18,60	18,60	18,60	18,60
Filett. UNC.....		Nr. 10	Nr. 12	1/4	5/16	3/8	7/16	1/2
Filetti per pollice	Nr	24	24	20	18	16	14	13
Dimensioni.....	mm	20x7	20x7	20x7	25x9	30x11	30x11	38x14
9364G	Cad.	18,60	18,60	17,70	20,20	22,40	26,10	29,20
Filett. UNC.....		9/16	5/8	3/4	7/8	1		
Filetti per pollice	Nr	12	11	10	9	8		
Dimensioni.....	mm	38x14	45x18	45x18	55x22	55x22		
9364G	Cad.	36,10	39,40	39,40	67,40	67,40		

9366G



Orig. Völkel - Art. 244

Descrizione di riferimento vedi Art. 9350G

FILETTATURA AMERICANA UNF conforme ANSI-B1.1

USO DESTRO

In acciaio SUPER-RAPIDO HSS, imbocco normale, per acciai con R fino a 800 N/mm².

Filett. UNF.....		Nr. 1	Nr. 2	Nr. 3	Nr. 4	Nr. 5	Nr. 6	Nr. 8
Filetti per pollice	Nr	72	64	56	48	44	40	36
Dimensioni.....	mm	16x5	16x5	16x5	20x5	20x5	20x5	20x7
9366G	Cad.	20,80	20,20	20,20	18,60	18,60	18,60	18,60
Filett. UNF.....		Nr. 10	Nr. 12	1/4	5/16	3/8	7/16	1/2
Filetti per pollice	Nr	32	28	28	24	24	20	20
Dimensioni.....	mm	20x7	20x7	20x7	25x9	30x11	30x11	38x10
9366G	Cad.	18,60	18,60	17,70	20,20	22,40	26,10	29,20
Filett. UNF.....		9/16	5/8	3/4	7/8	1		
Filetti per pollice	Nr	18	18	16	14	12		
Dimensioni.....	mm	38x10	45x14	45x14	55x16	55x16		
9366G	Cad.	36,10	39,40	39,40	67,40	67,40		

9368G



Orig. Völkel - Art. 254

Tipo chiuso, completamente rettificato DIN - EN 24231.

FILETTATURA GAS CILINDRICA G (BSP) conforme DIN 228-1

USO DESTRO

In acciaio SUPER-RAPIDO HSS, imbocco normale, per acciai con R fino a 800 N/mm².

Ø.....	poll	1/8	1/4	3/8	1/2	5/8	3/4	7/8
Filetti per pollice	Nr	28	19	19	14	14	14	14
Dimensioni.....	mm	30x11	38x10	45x14	45x14	55x16	55x16	65x18
9368G	Cad.	26,20	26,70	35,50	35,50	64,10	64,10	86,10
Ø.....	poll	1	1.1/8	1.1/4	1.3/8	1.1/2	1.3/4	2
Filetti per pollice	Nr	11	11	11	11	11	11	11
Dimensioni.....	mm	65x18	75x20	75x20	90x22	90x22	105x22	105x22
9368G	Cad.	86,10	145,00	145,00	253,00	253,00	434,00	485,00

9368M



INOX

Orig. Völkel - Art. 554

Descrizione di riferimento vedi Art. 9368G

FILETTATURA GAS CILINDRICA G (BSP) conforme DIN 228-1

USO DESTRO

In acciaio SUPER-RAPIDO HSS-E, imbocco corretto, per acciai INOX e acciai con R fino a 1200 N/mm².

Ø.....	poll	1/8	1/4	3/8	1/2	3/4	1		
Filetti per pollice	Nr	28	19	19	14	14	11		
Dimensioni.....	mm	30x11	38x10	45x14	45x14	55x16	65x18		
9368M	Cad.	46,30	50,40	85,10	85,10	142,00	215,00		

9370G



Orig. Völkel - Art. 236

Tipo chiuso, completamente rettificato.

FILETTATURA AMERICANA NPT - Conicità 1:16

USO DESTRO

In acciaio SUPER-RAPIDO HSS, imbocco normale, per acciai con R fino a 800 N/mm².

Ø.....	poll	1/8	1/4	3/8	1/2	3/4	1	1.1/4	1.1/2	2
Filetti per pollice	Nr	27	18	18	14	14	11 1/2	11 1/2	11 1/2	11 1/2
Dimensioni.....	mm	30x11	38x14	45x14	45x18	55x22	65x25	75x26	90x27	105x28
9370G	Cad.	63,30	77,50	98,30	102,00	157,00	233,00	274,00	448,00	615,00