

CHIAVI A BUSSOLA ATTACCO 1/2" DIN 3120-ISO 1174 (sockets)

Orig. Gedore - Art. 19

In acciaio al CROMO-VANADIO. Esecuzione cromata.
Con alloggiamenti all'interno dell'attacco per le sfere di fermo dei cricchi e leve.
DIN 3124, ISO 2725-1.
Tipo con esagono interno.

GEDORE

969RA



1/2"

3

Apertura.....	mm	8	9	10	11	12	13	14
Lungh. totale.....	mm	38	38	38	38	38	38	38
969RA	Cad.	12,90	12,90	12,90	13,10	13,30	13,70	14,40
Apertura.....	mm	15	16	17	18	19	20	21
Lungh. totale.....	mm	39	39	39	39	40	40	41
969RA	Cad.	14,60	14,80	15,40	15,80	16,10	16,80	18,00
Apertura.....	mm	22	23	24	25	26	27	28
Lungh. totale.....	mm	41	41	41	41	41	41	43
969RA	Cad.	18,20	18,50	18,50	20,10	20,50	23,60	26,70
Apertura.....	mm	29	30	32	33	34	36	
Lungh. totale.....	mm	43	43	44	44	44	44	
969RA	Cad.	26,90	26,90	27,30	29,10	29,10	39,30	

Orig. Gedore - Art. D19

Descrizione di riferimento vedi Art. 969RA
DIN 3124, ISO 2725-1 mis. in mm.
Tipo con poligono interno.

GEDORE

969RB



1/2"



Apertura.....	mm	8	9	10	11	12	13	14
Lungh. totale.....	mm	38	38	38	38	38	38	38
969RB	Cad.	12,90	12,90	12,90	13,10	13,30	13,70	14,40
Apertura.....	mm	15	16	17	18	19	20	21
Lungh. totale.....	mm	39	39	39	39	40	40	41
969RB	Cad.	14,60	14,80	15,40	15,80	16,10	16,80	18,00
Apertura.....	mm	22	23	24	25	26	27	28
Lungh. totale.....	mm	41	41	41	41	41	41	43
969RB	Cad.	18,20	18,50	18,50	20,10	20,50	23,60	26,70
Apertura.....	mm	29	30	32	33	34	36	
Lungh. totale.....	mm	43	43	44	44	44	44	
969RB	Cad.	26,90	26,90	27,30	29,10	29,10	39,30	
Apertura.....	poll	5/16	11/32	3/8	13/32	7/16	1/2	9/16
Lungh. totale.....	mm	38	38	38	38	38	38	38
969RB	Cad.	16,80	20,50	16,80	16,40	16,80	16,40	17,40
Apertura.....	poll	19/32	5/8	11/16	3/4	25/32	13/16	7/8
Lungh. totale.....	mm	39	39	39	40	40	41	41
969RB	Cad.	17,40	17,40	18,50	18,50	18,50	20,50	20,50
Apertura.....	poll	15/16	1	1.1/16	1.1/8	1.3/16	1.1/4	
Lungh. totale.....	mm	41	41	41	43	43	44	
969RB	Cad.	22,10	22,10	28,90	29,10	29,90	30,60	

Orig. Gedore - Art. 19L

Descrizione di riferimento vedi Art. 969RA
DIN 3124, ISO 2725-1.
Tipo lungo con esagono interno.

GEDORE

969RBE



1/2"

Apertura.....	mm	10	11	12	13	14	15	16
Lungh. totale.....	mm	77	77	77	77	77	77	77
969RBE	Cad.	33,90	33,90	35,10	35,10	37,10	37,10	37,80
Apertura.....	mm	17	18	19	21	22	24	27
Lungh. totale.....	mm	77	82	82	82	82	82	82
969RBE	Cad.	37,80	38,20	38,20	45,80	47,10	48,10	49,80
Apertura.....	mm	30	32	34				
Lungh. totale.....	mm	82	82	82				
969RBE	Cad.	52,40	56,30	58,90				

Aperture mm 16 - 18 - 21 con foro per leve.

Orig. Gedore - Art. D19L

Descrizione di riferimento vedi Art. 969RA
DIN 3124, ISO 2725-1.
Tipo lungo con poligono interno.

GEDORE

969RC



1/2"



Apertura.....	mm	10	12	13	14	15	16	17	18
Lungh. totale.....	mm	77	77	77	77	77	77	77	82
969RC	Cad.	33,90	35,10	35,10	37,10	37,10	37,80	37,80	38,20
Apertura.....	mm	19	21	22	24	27	30	32	34
Lungh. totale.....	mm	82	82	82	82	82	82	82	82
969RC	Cad.	38,20	45,80	47,10	48,10	49,80	52,40	56,30	58,90

Aperture mm 16 - 18 - 21 con foro per leve.

Tutte le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.

Prezzi in EURO - IVA esclusa